



BAND SAWS / JIG SAWS

PORTABLE BAND SAWS

6225
200/250 FPM

6226
250/200 FPM
WITH CASE



FEATURES:

- Cuts up to 3-1/2 in. x 4-1/2 in. rectangular stock and 3-1/2 in. round stock.
- 6.0/5.0 amp, AC only.
- Two speeds: 200 and 250 sfpm.
- Uses standard 44-7/8 in. x 1/2 in. x .020 in. band saw blades.

SPECIFICATIONS

Voltage	120 AC
Amps	6.0/5.0
Capacity in Rect. Stock	3-1/2 in x 4-1/2 in.
Capacity in Round Stock	3-1/2 in.
Cord Type	8 ft. Fixed
Construction Type	Grounded
Switch Type	Trigger
Length	20 in.
Weight	16 lbs.

DEEP CUT PORTABLE BAND SAW

6232-6
0-350 FPM
WITH CASE



FEATURES:

- Cuts up to 4-3/4 in. x 4-3/4 in. rectangular stock and 4-3/4 in. round stock.
- 6.0 amp, AC only.
- Trigger speed control: 0-350 sfpm.
- Uses standard 44-7/8 in. x 1/2 in. x .020 in. band saw blades.

SPECIFICATIONS

Voltage	120 AC
Amps	6.0
Capacity in Rect. Stock	4-3/4 in. x 4-3/4 in.
Capacity in Round Stock	4-3/4 in.
Cord Type	8 ft. Fixed
Construction Type	Grounded
Switch Type	Trigger
Length	19-3/4 in.
Weight	17 lbs.

6226 AND 6232-6 INCLUDE
Carrying case for band saws

ALL INCLUDE
14-tooth blade

ORBITAL JIG SAW

6268-21
0-3,000 SPM
WITH CASE



FEATURES:

- LED light for improved sightline.
- Powerful 6.5 amp motor.
- Orbital action with 4 adjustment levels and 1 in. stroke length for faster cutting.
- Variable speed trigger - 0-3,000 SPM.
- Variable speed dial for repetitive cuts.
- Quik-Lok™ blade change system.
- Keyless Shoe Adjustment - 45° in both directions.
- Precision roller blade guide for accurate cuts.
- Counter balanced for reduced vibration.
- Tachometer feedback for constant cutting speed.
- Cushion grip for superior gripping and control.

SPECIFICATIONS

Voltage	120 AC
Amps	6.5
Stroke Length	1 in.
Blade Type	T-Shank
Cord Type	12-2/3 ft. Fixed
Construction Type	Double Insulated
Switch Type	Trigger
Trigger Lock	On
Dial Speed Control	Yes
Keyless Blade Clamp	Yes
Orbital Action	Yes
Length	9-1/2 in.
Weight	6.4 lbs.

BODY GRIP ORBITAL JIG SAW

6276-21
500-3,000 SPM
WITH CASE



FEATURES:

- Powerful 6.2 amp motor.
- Orbital action with 4 adjustment levels for faster cutting.
- 7-setting dial speed control 500-3,000 SPM.
- Quik-Lok™ blade change system.
- Keyless 45° bevel adjustment.
- 10-position dust blower and built-in dust collection port for easy attachment to vacuum.
- Die cast aluminum shoe and all metal gear case.
- Low position roller guide for blade stability and precision cuts.
- Counter balanced for reduced vibration.

SPECIFICATIONS

Voltage	120 AC
Amps	6.2
Stroke Length	1 in.
Blade Type	T-Shank
Cord Type	9-1/2 ft. Fixed
Construction Type	Double Insulated
Switch Type	Trigger
Trigger Lock	On
Dial Speed Control	Yes
Keyless Blade Clamp	Yes
Orbital Action	Yes
Length	11-3/4 in.
Weight	5.0 lbs.

BOTH INCLUDE

- Anti-splintering device
- Plastic shoe cover
- Two blades
- Dust shield
- Carrying case



FEATURES:

- Custom molded, lightweight, impact resistant, rust proof plastic.
- Ideal for tool and accessory storage.

