



# D-HANDLE, RIGHT ANGLE AND CLOSE QUARTER DRILLS

## 1/2 IN. D-HANDLE DRILLS

### 1001-1

Variable speed – 0-600 rpm  
Triple gear reduction  
8' fixed cord

### 1007-1

Variable speed – 0-600 rpm  
Triple gear reduction  
8' Quik-Lok® cord

### 1101-1

Single speed – 500 rpm  
Triple gear reduction  
8' fixed cord

### 1107-6

Variable speed – 0-500 rpm  
Triple gear reduction  
8' Quik-Lok cord

### 1250-1

Variable speed – 0-1,000 rpm  
Double gear reduction  
8' Quik-Lok cord



#### ALL INCLUDE

Side handle  
Chuck key with holder

#### COMMON FEATURES:

- 1/2 in. capacity in steel.
- Powerful 7 amp Milwaukee built motor.
- Reversing speed.

#### COMMON SPECIFICATIONS

Voltage ..... 120 AC  
 Chuck Size ..... 1/2 in.  
 Chuck Type ..... Keyed  
 Spindle ..... 1/2 in.-20  
 Construction Type ..... Grounded  
 Length ..... 14-3/4 in.  
 Tool Weight ..... 6.8 lbs.

#### ACCESSORIES



#### Quik-Lok Cord



#### Right Angle Drive



#### Quick Change Chuck

Converts 3 jaw chuck into a 7/16 in. quick change chuck (1101-1 and 1250-1)



#### Angle Drill Kit 33 Degree

- Stretches drilling reach up to 30 in.
- Allows drilling up to 2-9/16 in. diameter holes.
- Use 33 degree angle drive with 30 in. extension only.

## 1/2 IN. D-HANDLE RIGHT ANGLE DRILL KITS

### 3002-1

Variable speed – 0-400/0-900 rpm  
Handles up to 2-9/16" selffeed bit  
8' fixed cord

### 3102-6

Two speed – 335 and 750 rpm  
Handles up to 2-9/16" selffeed bit  
8' fixed cord

### 3107-6

Variable speed – 0-335/0-750 rpm  
Handles up to a 4-5/8" selffeed bit  
8' Quik-Lok cord



#### ALL INCLUDE

Carrying case  
RAD assembly  
Side handle  
9/16" open end wrench  
3/16" socket wrench  
Chuck remover bar

#### COMMON SPECIFICATIONS

Voltage ..... 120 AC  
 Chuck Size ..... 1/2 in.  
 Chuck Type ..... Keyed  
 Gear Train ..... Quadruple  
 Construction Type ..... Grounded  
 Length ..... 16-3/4 in.  
 Tool Weight ..... 10.3 lbs.

#### ACCESSORIES



#### Ship Auger Bit (3107-6 only)

- 1" diameter, 6" overall length.
- 1/2" shank, 4" twist.

**Selffeed Bits** – Electricians and Plumbers rely on Selffeed Bits for large hole drilling in wood.



- 1-1/2", 2", 2-1/8", 2-1/2" and 2-9/16" bit diameters available.
- 7/16" hex shank.



- 4-5/8" diameter.
- 3 milled flat shank.

## CLOSE QUARTER DRILLS

### 0375-6

0-1,300 rpm, reversing  
3/8" chuck  
6-1/2" long, 3 lbs.

### 0379-1

0-750 rpm, reversing  
1/2" chuck  
6-3/4" long, 3.5 lbs.

#### COMMON FEATURES:

- 3.5 amp motor.
- Trigger speed control.
- Heavy-duty industrial chuck.
- 55° angled chuck for easy access to tight places.
- Ideal for working in tight spaces where a full size drill doesn't fit.



#### BOTH INCLUDE

Chuck key with holder

#### COMMON SPECIFICATIONS

Voltage ..... 120 AC  
 Chuck Type ..... Keyed  
 Spindle ..... 1/2 in.-20  
 Gear Train ..... Double  
 Cord Type ..... 7 ft. Fixed  
 Construction Type ..... Double Insulated  
 Spindle Lock ..... No  
 Soft Grip Handle ..... No