

MITER, CHAIN AND CUT-OFF SAWS

10 IN. MAGNUM® SLIDE COMPOUND MITER SAW

6497-6 4.800 RPM **INCLUDES**

10 in. carbide tipped blade Extension kit Vise

Dust bag Blade wrench

FEATURES:

- Powerful 15 amp motor.
- Large cutting capacity:
 - Crosscut up to 3-1/2" x 12".
 - Cut 3-7/16" x 8-3/4" at 45 degree miter. Cut 2-1/8" x 8-3/4" at 45 degree x 45
 - degree compound.
- Wide miter angles from 51 degrees left to 59 degrees right. Positive stops at 0, 15, 22.5, 30 and 45 degrees left and right.
- Bevels angles from 48 degrees left and 3 degrees right. Positive bevel stops at 0 degrees and 45 degrees.



SPECIFICATIONS

Voltage
Amps
Blade Size
Spindle
Vertical Capacity
(Baseboard against fence) 4-1/4 in
Vertical Capacity
(Crown molding nested vertically) 5-1/2 in
Horizontal Capacity
(Baseboard lying flat 12-3/8 in
0° Miter/0° Bevel (Max length) 4 x 12
0° Miter/0° Bevel (Max width)
45° Miter/0° Bevel (Max width) 4 x 8
Max 0° Miter/45° Bevel (Max width) 2 x 10
Max 45° Miter/45° Bevel (Max width) 2 x 8
Length
Weight

ELECTRIC CHAIN SAW

6215

INCLUDES

16 in. sprocket tip bar 1,800 FPM 3/8 in. pitch chain 33mm wrench

Screwdriver Scabbard

FEATURES:

- Powerful 2.25 maximum horsepower motor, 13 amp.
- 16 inch bar, 1,800 feet per minute chain speed.
- Automatic oiling.
- Adjustable clutch protects motor and mechanism from harmful binding.



SPECIFICATIONS

Voltage	120 AC
Amps	13.0
Bar Size	16 in.
Max. HP	2.2
Cord Type	1 ft. Fixed
Construction Type	Double Insulated
Switch Type	Trigger
Oil Tank Capacity	6-1/2 oz.
_ength	8-3/4 in.
Neight	
•	

14 IN. ABRASIVE CUT-OFF MACHINE

6176-20

3.900 RPM For use with abrasive cut-off wheels (14" x 3/32" x 1")

INCLUDES

Vise Abrasive wheel

- 15 amp, 2,400 watts/3.2 maximum horsepower power output.
- 5-inch pipe cutting capacity.
- Heavy-duty cast iron base.
- Spindle lock for convenient changing of abrasive wheels.
- Rugged steel and high strength nylon construction keeps durability high and weight low.
- All ball bearing construction for longer life. / Easy access brushes.
- One piece carrying handle.
- Wheel rotation directs particles away from operator.
- Arm locks down for easy portability.



 Wheel Size
 14 in.

 Max. HP
 3.2
 Spindle Lock Yes

Spindle Lock Yes

Bevel Capacity 45°

Capacity in O.D. Pipe 5 in.

Capacity in Bar Stock 3-5/8 in.

Capacity in Square Stock 5 in. Maximum Opening 9 in.