

SCREWDRIVERS

DRYWALL SCREWDRIVER

6742-20 0-4000 RPM



6740-20

0-2500 RPM

BOTH INCLUDE

Belt clip Phillips bit No. 2 reduced diameter Magnetic bit holder 1/4 in. x 3 in. Drywall locator assembly



COMMON FEATURES:

- Powerful 6.5 amp motor, variable speed control.
- Ramp-off depth locator for easy depth adjustments.
- All metal gear case and diaphragm.
- 10 ft. 2-wire rubber cord.
- Ergonomic tactile grip and two finger trigger for user comfort and balance.
- Removable belt clip with bit storage.

SPECIFICATIONS

Voltage	120 AC
Amps	6.5
Drive Size	1/4 in. Hex
Max. HP	0.9
Cord Type	10 ft. Fixed
Construction Type	. Double Insulated
Switch Type	Trigger
Trigger Lock	On
Soft Grip Handle	Yes
Clutch	Snap-Action
Spindle Offset	0.92 in.
Length (6742-20)	12-3/4 in.
Weight (6742-20)	3.5 lbs.
Length (6740-20)	13-1/8 in.
Weight (6740-20)	3.7 lbs

Phillips Bit No. 2 Reduced Diameter Magnetic Bit Holder 1/4 in. x 3 in.



FEATURES:

- Screw shooter bit.
- 1-inch length.
- Reduced phillips bit.
- Screw size #2.



FEATURES:

- Magnetic bit holder.
- 1/4 inch
- 3-inch length.
- Screw shooter accessory.

Drywall Locator Assembly



FEATURES:

- Patented ramp-off locator.
- Insert molded, extra hard, stainless steel tip.
- Acetal resin formulated for maximum toughness but lightweight.
- Positive depth selection indexes 1/64 in. per two clicks.

SELF DRILL FASTENER SCREWDRIVER

6790-20

0-2.500 RPM

FEATURES:

- Powerful 6.5 amp motor, variable speed control.
- Ramp-off depth locator for easy depth adjustments.
- All metal gear case and diaphragm.
- 10 ft. 2-wire rubber cord.
- Ergonomic tactile grip and two finger trigger for user comfort and balance.
- Removable belt clip with bit storage.



INCLUDES

Belt clip TEK locator assembly 5/16 in. magnetic hex socket

TEK Locator Assembly



FEATURES:

- Patented ramp-off locator.
- Acetal resin formulated for maximum toughness but lightweight.
- Positive depth selection indexes 1/64 in. per two clicks.

SPECIFICATIONS

Voltage	120 AC
Amps	6.5
Drive Size	1/4 in. Hex
Max. HP	0.9
Cord Type	10 ft. Fixed
Construction Type	Double Insulated
Switch Type	Trigge
Trigger Lock	
Soft Grip Handle	Yes
Clutch	
Spindle Offset	0.92 in
Length	12-1/8 in. in.
Weight	

5/16 in. Magnetic Hex Socket



FEATURES:

■ 5/16 in. hex size.

Clinton, MD (301) 877-8640

Combines driver and socket in one piece.

