



SHEARS, NIBBLER AND ROUTERS

18-GAUGE SHEARS

6852-20
0-2,500 SPM

INCLUDES
Hex wrench

FEATURES:

- 6.8 amp Milwaukee motor, trigger speed control: 0-2,500 rpm spindle speed.
- 360° swivel head.
- Ergonomic tactile grip for optimal user comfort.
- 10 ft. flexible durable runner cord.



SPECIFICATIONS

Voltage 120 AC
Amps 6.8
Capacity in Steel 18-Ga.
Capacity in Stainless 20-Ga.
Cord Type 10 ft. Fixed
Construction Type Double Insulated
Switch Type Trigger
Trigger Lock On
Minimum Cutting Radius 7 in.
Length 12-1/4 in.
Weight 4.1 lbs.

16-GAUGE NIBBLER

6890
1,900 SPM

INCLUDES
Punch
Die
Allen wrench
Plate wrench

FEATURES:

- 3.8 amp, 1,900 spm.
- Cuts up to 7 ft. per minute.
- 0.87 in. starting hole required.
- AC/DC paddle switch.



SPECIFICATIONS

Voltage 120 AC/DC
Amps 4.0
Capacity in Steel 16-Ga.
Capacity in Stainless 18-Ga.
Cord Type 8 ft. Fixed
Construction Type Double Insulated
Switch Type Paddle
Minimum Cutting Radius 1-3/4 in.
Starting Hole 7/8 in.
Length 11-1/4 in.
Weight 4.8 lbs.

1-3/4 MAX HP BODYGRIP® ROUTER

5615-20
24,000 RPM

INCLUDES
Two 1-1/8 in. collet wrenches
1/2 in. collet
1/4 in. collet

FEATURES:

- Exclusive BodyGrip® design.
- 1-3/4 max. HP, 11 Amp, Milwaukee motor.
- Exclusive linear depth adjustment system.
- 1/4 in. and 1/2 in. premium self-releasing collets.



SPECIFICATIONS

Voltage 120 AC/DC
Collet Diameter 1/4 in. - 1/2 in.
Amps 11.0
Cord Type 8 ft. Fixed
Construction Type Double Insulated
Switch Type Rocker
Dial Speed Control No
Handle Style BodyGrip
Electronic Feedback No
Depth Adj. Range 1-21/32 in.
Sub Base Dia. 6 in.
Height 8-1/2 in.
Weight 8.8 lbs.

2-1/4 MAX HP EVS BODYGRIP® ROUTER

5616-20
10,000-24,000 RPM

INCLUDES
Two 1-1/8 in. collet wrenches
1/2 in. collet
1/4 in. collet
T-Handle wrench

FEATURES:

- Exclusive BodyGrip® design.
- 2-1/4 max. HP Milwaukee motor.
- Premium electronic motor feedback maintains speed and power under load.
- 36-speed, electronic variable speed with soft start.
- Micro-fine linear depth adjustment to within 1/64 in.
- Exclusive above-the-table depth adjustment system.
- Exclusive motor contamination shield minimizes damage, maximizes airflow.



SPECIFICATIONS

Voltage 120 AC
Collet Diameter 1/4 in. - 1/2 in.
Amps 13.0
Cord Type 8 ft. Fixed
Construction Type Double Insulated
Switch Type Double Insulated
Switch Type Rocker
Dial Speed Control Yes
Handle Style BodyGrip
Electronic Feedback Yes
Depth Adj. Range 1-21/32 in.
Sub Base Dia. 6 in.
Height 8-1/2 in.
Weight 8.8 lbs.

