



STRAIGHT AND DIE GRINDERS

STRAIGHT GRINDERS

5211

3" Diameter
11 AMPS
14,500 RPM

INCLUDES

9/16 in. and 1 in. wrenches
Grinding wheel and guard



5223

5" Diameter
12 AMPS
7,000 RPM

INCLUDES

9/16 in. and 1 in. wrenches
Grinding wheel and guard



5243

6" Diameter
15 AMPS
5,500 RPM

INCLUDES

1-1/16 in. and spanner wrenches
Grinding wheel and guard



FEATURES:

- Coated spindle housing for cool gripping surface.
- Hinged face plate for quick easy wheel replacement. (5211 & 5243)
- Hardened helical-cut alloy steel gears and shaft. (5223)

ACCESSORIES



Twist Knot Wheel
3 Inch Standard



Grinding Wheel
3x1/2, 36/60 Grit



Buffing Wheel
5 Inch

COMMON SPECIFICATIONS

Voltage 120 AC
 Cord Type 9 ft. Fixed
 Switch Type Trigger
 Trigger Lock On

5211 SPECIFICATIONS

Wheel Size 1/2 in. x 3 in.
 Spindle 3/8 in.-24
 Hole Dia. 3/8 in.
 Length 21 in.
 Weight 7.8 lbs.

5223 SPECIFICATIONS

Wheel Size 1 in. x 5 in.
 Spindle 5/8 in.-11
 Hole Dia. 5/8 in.
 Length 20 in.
 Weight 10.3 lbs.

5243 SPECIFICATIONS

Wheel Size 1 in. x 6 in.
 Spindle 5/8 in.-11
 Hole Dia. 5/8 in.
 Length 22 in.
 Weight 16.5 lbs.

DIE GRINDERS

5194

4.5 AMPS
21,000 RPM



5196

11 AMPS
14,500 RPM



INCLUDES

1/4 in. collet
1 1/16 in. open end wrench
1/2 in. open end wrench
1 in. open end wrench (5196)

FEATURES:

- 1/4 in. collet standard equipment, 1/8 in. collet available.
- All ball and roller bearings.

5194 SPECIFICATIONS

Voltage 120 AC/DC
 Cord Type 8 ft. Fixed
 Switch Type Paddle
 Max. Cap. Reinforced Grinding Wheels . . 2 in.
 Max. Cap. Mounted Wheels & Points. 1-5/8 in.
 Length 13-1/2 in.
 Weight 4.5 lbs.

5196 SPECIFICATIONS

Voltage 120 AC/DC
 Cord Type 9 ft. Fixed
 Switch Type Trigger
 Trigger Lock On
 Max. Cap. Reinforced Grinding Wheels . . 2 in.
 Max. Cap. Mounted Wheels & Points. . . . 2 in.
 Length 21-1/2 in.
 Weight 7.8 lbs.

